



Controlled Vocabulary Enumeration Values for CVEnumISMatomicEnergyMarkings

CVEnumISMatomicEnergyMarkings.XML

Version 1

27 February 2012

Distribution Notice:

This document has been approved for Public Release and is available for use without restriction.

Table of Contents

Chapter 1 - CVEnumISMatomicEnergyMarkingsValues for ISM	1
1.1 - Permissible Values	1
1.2 - CVEnumISMatomicEnergyMarkings Values maxLength:	2

List of Tables

Table 1 - CVEnumISMatomicEnergyMarkings Patterns	1
Table 2 - CVEnumISMatomicEnergyMarkings Values	1

Chapter 1 - CVEnumISMatomicEnergyMarkingsValues for ISM

1.1 - Permissible Values

The permissible values for this simple type are defined in the Controlled Value Enumeration: CVEnumISMatomicEnergyMarkings.xml

Table 1 - CVEnumISMatomicEnergyMarkings Patterns

Classification of Row	Pattern	Classification of Pattern	Documentation
	RD-SIGMA-#, # represents the SIGMA number which may be 14, 15, 18, or 20.		
	FRD-SIGMA-#, # represents the SIGMA number which may be 14, 15, 18, or 20.		

Table 2 - CVEnumISMatomicEnergyMarkings Values

Classification of Row	Value	Classification of Value	Documentation
	RESTRICTED DATA		
	RD-CRITICAL NUCLEAR WEAPON DESIGN INFORMATION		
	FORMERLY RESTRICTED DATA		
	DoD CONTROLLED NUCLEAR INFORMATION		

Classification of Row	Value	Classification of Value	Documentation
	DoE CONTROL LED NUCLEAR INFORMAT ION		
	TRANSCLA SSIFIED FOREIGN NUCLEAR INFORMAT ION		

1.2 - CVEnumISMatomicEnergyMarkings Values maxLength:

1000