



Controlled Vocabulary Enumeration Values for CVEnumISMatomicEnergyMarkings

CVEnumISMatomicEnergyMarkings.XML

Version 1

17 July 2012

Distribution Notice:

This document has been approved for Public Release and is available for use without restriction.

Table of Contents

Chapter 1 - CVEnumISMatomicEnergyMarkingsValues for ISM	1
1.1 - Permissible Values	1
1.2 - CVEnumISMatomicEnergyMarkings Values maxLength:	2

List of Tables

Table 1 - CVEnumISMatomicEnergyMarkings Patterns	1
Table 2 - CVEnumISMatomicEnergyMarkings Values	1

Chapter 1 - CVEnumISMatomicEnergyMarkingsValues for ISM

1.1 - Permissible Values

The permissible values for this simple type are defined in the Controlled Value Enumeration:
CVEnumISMatomicEnergyMarkings.xml

Table 1 - CVEnumISMatomicEnergyMarkings Patterns

Classification of Row	Pattern	Classification of Pattern	Documentation
	RD-SIGMA-#, # represents the SIGMA number which may be 14, 15, 18, or 20.		
	FRD-SIGMA-#, # represents the SIGMA number which may be 14, 15, 18, or 20.		

Table 2 - CVEnumISMatomicEnergyMarkings Values

Classification of Row	Value	Classification of Value	Documentation
	RESTRICT ED DATA		
	RD- CRITICAL NUCLEAR WEAPON DESIGN INFORMAT ION		
	FORMERL Y RESTRICT ED DATA		
	DoD CONTROL LED NUCLEAR INFORMAT ION		

Classification of Row	Value	Classification of Value	Documentation
	DoE CONTROLLED NUCLEAR INFORMATION		
	TRANSCLA SSIFIED FOREIGN NUCLEAR INFORMATION		

1.2 - CVEnumISMatomicEnergyMarkings Values maxLength:

1000